

1 1/2" All-PüR® Pumps

Engineered for maximum fluid and chemical compatibility. Heavy duty, stall free, non-metallic air section ensures stall free & freeze free operation. Rugged valve system allows operation under a variety of conditions, ranging from clean fluids to slurries, to solids applications. Bolted design provides ease of maintenance and leak free operation. Available in a variety of materials and options.

- Suitable for clean fluids, slurries or up to 1/4" solids
- All-P
 ür® FDA Elastomers and Electropassivated Stainless Available
- Heavy duty air valve
- Available in metallic and non-metallic wetted components
- Muffler included

1 1/2" All-PüR® Pumps

Part No.	Fluid Chambers	Diaphragms	Valve/Ball	Valve Seats	O-Rings	Connection Type
SB- 15- X44	Electropolished and Passivated 316 SS	FDA Hytrel®FDA accepted Hytrel®.	FDA NitrileFDA accepted Nitrile.	Stainless SteelCorrosion resistant steel.	FDA NitrileFDA accepted Nitrile.	2" Tri-Clamp
SE- 15- X44	Electropolished and Passivated 316 SS	FDA Santoprene®	FDA Santoprene®FDA accepted Santoprene®.	Stainless SteelCorrosion resistant steel.	FDA EPDMFDA accepted EPDM.	2" Tri-Clamp
SP- 15- X44	Electropolished and Passivated 316 SSCorrosion resistant Steel that has been electropolished and passivated. Suitable for food and sanitary applications.	FDA PTFE	FDA PTFE	Stainless Steel	FDA PTFE	2" Tri-Clamp