



2" All-Pūr® Pumps

Engineered for maximum fluid and chemical compatibility. Heavy duty, stall free, non-metallic air section ensures stall free & freeze free operation. Rugged valve system allows operation under a variety of conditions, ranging from clean fluids to slurries, to solids applications. Bolted design provides ease of maintenance and leak free operation.

Available in a variety of materials and options.

- Suitable for clean fluids, slurries or up to 1/4" solids
- All-Pūr FDA Elastomers and Electropassivated Stainless Available
- Heavy duty air valve
- Available in metallic and non-metallic wetted components
- Muffler included

2" All-Pūr® Pumps

Part No.	Fluid Chambers	Diaphragms	Valve/Ball	Valve Seats	O-Rings	Connection Type
SB-20-X44	Electropolished and Passivated 316 SS Corrosion resistant Steel that has been electropolished and passivated. Suitable for food and sanitary applications.	FDA Hytrel® FDA accepted Hytrel®.	FDA Nitrile FDA accepted Nitrile.	Stainless Steel Corrosion resistant steel.	FDA Nitrile FDA accepted Nitrile.	2 1/2" Tri-Clamp
SE-20-X44	Electropolished and Passivated 316 SS	FDA Santoprene® FDA accepted Santoprene®.	FDA Santoprene® FDA accepted Santoprene®.	Stainless Steel	FDA EPDM	2 1/2" Tri-Clamp
SP-20-X44	Electropolished and Passivated 316 SS	FDA PTFE	FDA PTFE	Stainless Steel	FDA PTFE	2 1/2" Tri-Clamp