





West Chicago, IL 60185 Phone: 630-562-2700 www.triadboiler.com

TRIAD BOILER SYSTEMS, INC. SERIES 2000 SPACE HEAT BOILER









Note: Dimensions subject to change without notice.



TRIAD BOILER SYSTEMS, INC. SERIES 2000 SPACE HEAT BOILER (Model SH)

The Series 2000 is a steel vertical firetube packaged boiler with a water-backed combustion chamber equipped with high-efficiency turbulators. Boilers come fully wired.

STANDARD EQUIPMENT:

Low/High/Off Riello (UL Listed)
Honeywell Control Center
Low Water Cut-Off
Combination Pressure/Temperature Gauge
Operating Light
Relief Valve
Second Safety High Limit with Manual Reset
Vessel Pressure Rating of 100 PSI
B&G Series 60 Circ Pump (Shipped Loose)

OPTIONAL EQUIPMENT:

Gas Fired (NG or Propane), Oil Fired, or Dual Fuel Burners UL, IRI, FM and CSD-1 Compliance Low/High/Low and Modulating Gas Trains Sealed Combustion Air Intake Barometric Dampers

SPECIFICATIONS:

Input BTU/Hr	Output BTU/Hr	Efficiency	
1,800,000	1,494,000	83.0%	
, ,	, ,		
1,900,000	1,577,000	83.0%	
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	, , , , , , , , , , , , , , , , , , , ,		
2,000,000	1,660,000	83.0%	
, ,	, ,		
2,100,000	1,172,200	82.0%	
_,,	1,11=,=11		
2,200,000	1,804,000	82.0%	
,,	, , , , , , , , , , , , , , , , , , , ,		
2,300,000	1,886,000	82.0%	
2,000,000	.,550,000	02.070	

Note: Typical for Natural Gas. - Oil or LP burner data may vary.

APPLICATIONS:

Space Heating and Process Water - typically 140°F - 210°F

CLEARANCES & CONNECTIONS:

Clearance recommended between boilers - 6"; From front of burner for service - 10". Supply & Return Openings - 3.00"

CONTROL:

The Series 2000 can operate on its own controls, but a TRIAD microprocessor control panel is recommended for sequencing more than two boilers to minimize run-time and fuel usage.

Flue: Category I when applied appropriately.

POWER: 120V, 60Hz, Single Phase, fused for 30 amps. Min / Max gas pressure, typically 8.0" / 14" WC

WEIGHT/VOLUME:

Shipping Weight – 2000 lbs. Water Volume – 149 gallons

Factory built copper or steel mains available upon request. ALL BURNER EQUIPMENT UL APPROVED

	TRIAD	BOIL	ER	REPRE	SENTA	ATIVE:
--	-------	------	-----------	-------	-------	--------

TRIAD Boiler Systems, Inc.

West Chicago, IL 60185 Phone: 630-562-2700 Fax: 630-562-2800 Web: www.triadboiler.com