Freedom LFF8

Progressive Cavity Pump

Features

- * Handles majority of sanitary applications
- * Interchangeable parts with other manufacturers
- * Various sizes to fit the best for your application
- * Designed to handle viscous materials
- * Self-priming capabilities
- Can provide continuous flow for metered applications

Pump Description

The Liberty Process Equipment Freedom Series is your best choice for Stainless Steel Sanitary Progressive Cavity Pump applications. Designed for food-grade installation, these pumps have been designed to handle fluids as thin as alcohol, spirits and soups to viscous icings, yeast and ice cream. The LFF8 model is an ideal solution for meat and chicken processing in the livestock processing industry and comes with a 4" Triclamp connection standard.

The Liberty Freedom Series of Sanitary progressive Cavity Pumps offer several important advantages over other types of positive displacement sanitary food grade pumps like Rotary lobe Pumps. Liberty PC Pumps have only one (1) shaft seal to maintain and do not have complicated complicated timing gears. Liberty Freedom Series Pumps are designed for quick disassembly for cleaning and sterilizing by hand. No additional tools for cleaning are required.

Freedom Series pumps are made with highly polished 316 Stainless Steel wetted parts. Elastomers are offered in Sanitary Buna, EPDM and Fluroelastomer. Stock pumps are carried with food grade Packing Seal type, but can be retrofitted with a Mechanical Seal (Single or Double). Pumps are equipped with Tri-Clamp Connections and a Clean-In-Place connection can be added. Hopper Feed pumps are also available for viscous material handling. Liberty also can manufacture the Freedom Series pump you purchase as a complete package including base, motor and any other requirements you may have per application.

Contact a Liberty Process representative today for more information about the Freedom Series for your sanitary pump application. Liberty Freedom Series LFF8 Progressive Cavity Sanitary Parts also work as an aftermarket pump part solution with the Moyno™ FF8 and the Tarby™ TFF8 Series.

Contact a Liberty Process representative today for more information about the Freedom Series

Materials


Rotor: Stainless Steel Chrome Plated

Stator: Food Grade Buna Nitrile, Viton™, EPDM

Motor: 3, 5, and 7.5 hp Inlet: 4" Triclamp Outlet: 4" Triclamp

Bases: Steel and Plastic





Curves



Single Stage



Double Stage

Please Click the Icon

Drawings




Single Stage



Double Stage Please Click the Icon

Click To Visit www.libertyprocess.com >>








Liberty Process Equipment, Inc. 2525 S Clearbrook Dr. Arlington Heights, IL 60005-4623 P-(847) 640-7867 F-(847) 640-7855 sales@libertyprocess.com

Type FF & FG


Suction and discharge connections are bevel seat with standard Acme sanitary threads.



Pump	AA	Α	В	СР	D	E	F	F2	G	Н	K	М	N	0	Р	Q	R	S	T	U	V	W	Z	Key	Disc	LBS.
1FF4	4 7/8	6 1/4	15 ½	32 9/16	4 7/8	14	14	5	1/2	7/16	2	18	3	7 7/8	-	-	7 1/16	-	-	15/16	-	-	-	½ 11/8	2	52
1FF6	6 5/8	8 ½	19	41	6 1/4	3 ½	17	7	5/8	11/16	2 ½	21 7/8	4 3/8	10 ¾	-	-	8	-	-	1 1/8	-	-	-	½ 1/8	2 ½	117
1FF8	8 5/8	11	26 ½	54 3/8	8	4 1/2	24	11	3/4	13/16	3	27 ½	4 ½	14	-	-	8 ½	-	-	1 3/8	-	-	-	3/8 3/16	4	273
1FF10	10 ¼	11	29 1/4	60 5/16	9 ¾	4 ½	26 1/4	12	1 1/8	13/16	3	31 3/8	5	15 ¾	-	-	10 9/16	-	-	1 7/8	-	-	-	½ 1/4	4	535
1FF10H	10 1/4	11	29 1/4	60 9/16	9 ¾	4 ½	26 1/4	12	1 1/8	13/14	3	31 5/8	5	15 ¾	-	-	10 13/16	-	-	1 7/8	-	-	-	½ 1/4	4	535

Freedom 1LFF8


RPM	100	300	500	700	900	
NPSH REQ'D	.8	2.2	3.7	6.9	10.5	
MIN. HP	1/2	11/2	2	3	-5	





Freedom 2LFF8

RPM	100	300	500	700	900	
NPSH REQ'D	.8	2.2	3.7	6.9	10.5	
MIN. HP	11/2	3	5	7 1/2	71/2	





Inc. Ph. (847)-640-7867 rive Fax. (847)- 640-7855 www.libertyprocess.com